



Product Service

Attestation of Conformity

No. E8A 17 11 99312 018

Holder of Certificate: **Solar Solutions GmbH**
Schneckenhofstrasse 19
60596 Frankfurt am Main
GERMANY

Name of Object: **Converter**
(PV grid-interactive inverter)

Model(s): **AS-IC01-4000-2, AS-IC01-5000-2, AS-IC01-6000-2,**
AS-IC01-4000, AS-IC01-5000,
AS-IC01-8000-2, AS-IC01-10000-2

Description of Object: MPPT Voltage Range : 200-800Vd.c.
(See page 2-3 for details)
Protection Class : I

Tested according to: EN 61000-6-3:2007/A1:2011
EN 61000-6-2:2005

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with all essential requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 687721700901A

Date, 2017-11-10


(Paul Yu)



CE After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. That declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

Page 1 of 3

Attestation of Conformity
No. E8A 17 11 99312 018



Product Service

Model	AS-IC01-4000-2	AS-IC01-5000-2	AS-IC01-6000-2
Vmax PV	900 Vd.c.	900 Vd.c.	900 Vd.c.
MPPT voltage range	200 – 800 Vd.c.	200 – 800 Vd.c.	200 – 800 Vd.c.
MPPT voltage range (full load)	210 – 800 Vd.c.	260 – 800 Vd.c.	310 – 800 Vd.c.
Isc PV	2x11 Ad.c.	2x11 Ad.c.	2x11 Ad.c.
Max. continuous PV input current	2x10 Ad.c.	2x10 Ad.c.	2x10 Ad.c.
MPPT tracker number Strings/string number per tracker	2 / 2	2 / 2	2 / 2
Max. continuous output current	6.4 Aa.c.	8 Aa.c.	9.6 Aa.c.
Nominal output voltage	3/N/PE, 230/400 Va.c.	3/N/PE, 230/400 Va.c.	3/N/PE, 230/400 Va.c.
Power factor, adjustable	0.9 leading~0.9 lagging	0.9 leading~0.9 lagging	0.9 leading~0.9 lagging
Nominal output frequency	50 Hz	50 Hz	50 Hz
Max. continuous output power	4000 VA	5000 VA	6000 VA
Operating temperature range	-25°C to +60°C	-25°C to +60°C	-25°C to +60°C
IP class	IP65	IP65	IP65
Protective class	I	I	I

Attestation of Conformity
No. E8A 17 11 99312 018



Product Service

Model	AS-IC01-4000	AS-IC01-5000	AS-IC01-8000-2	AS-IC01-10000-2
Vmax PV	900 Vd.c.	900 Vd.c.	1000 Vd.c.	1000 Vd.c.
MPPT voltage range	200 – 800 Vd.c.	200 – 800 Vd.c.	200 – 800 Vd.c.	200 – 800 Vd.c.
MPPT voltage range (full load)	400 – 800 Vd.c.	450 – 800 Vd.c.	350 – 800 Vd.c.	400 – 800 Vd.c.
Isc PV	13 Ad.c.	13 Ad.c.	2x13 Ad.c.	2x14 Ad.c.
Max. continuous PV input current	12 Ad.c.	12 Ad.c.	2x12 Ad.c.	2x12.5 Ad.c.
MPPT tracker number / String number per tracker	1 / 1	1 / 1	2 / 2	2 / 2
Max. continuous output current	6.4 Aa.c.	8 Aa.c.	12.5 Aa.c.	14 Aa.c.
Nominal output voltage	3/N/PE, 230/400 Va.c.	3/N/PE, 230/400 Va.c.	3/N/PE, 230/400 Va.c.	3/N/PE, 230/400 Va.c.
Power factor, adjustable	0.9 leading~0.9 lagging	0.9 leading~0.9 lagging	0.9 leading~0.9 lagging	0.9 leading~0.9 lagging
Nominal output frequency	50 Hz	50 Hz	50 Hz	50 Hz
Max. continuous output power	4000 VA	5000 VA	8800 VA	9800 VA
Operating temperature range	-25°C to +60°C	-25°C to +60°C	-25°C to +60°C	-25°C to +60°C
IP class	IP65	IP65	IP65	IP65
Protective class	I	I	I	I